



10kg Fk-5-1-12 Novec 1230 Extinguisher Exhaust Hanging Type Fire Extinguisher

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: xinlin
- Certification: ISO9001,CE,CCCF,examination report
- Model Number: XQFC10/1.6-XL
- Minimum Order Quantity: 10 set system
- Price: negotiation
- Packaging Details: Plywood outer box with bubble bag or paper
- Delivery Time: 10-15 working days after payment or receipt of L/C
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 30000 sets per week



Product Specification

- Color: Red
- Capacity: 6kg, 8kg, 10kg, 20kg, 30kg
- Feature: Clean Gas And Environmental Friendly
- Body Material: Steel Cylinder
- Medium: Novec1230
- Object: Class A, B, C, E Fires
- High Light: 10kg Novec 1230 Fire Suppression
- Starting Mode: 68°C Temperature Sensing Fire Suppression
- Highlight: **novec 1230 extinguisher, novtec 1230 exhaust, novtec 1230 fk-5-1-12**

Product Description

Product description

Factory Customise 10kg Fk-5-1-12 Hanging Type Fire Extinguisher for Valuable Instrument Room

The hanging novect 1230 (Fk-5-1-12) fire extinguisher is a special fire extinguishing equipment, its main characteristics and use are as follows:
Features:

Efficient fire suppression: novect 1230 fire extinguishing agent has the ability to quickly suppress flames, which can extinguish fires in a short time and reduce the damage caused by fires.

Environmentally friendly and harmless: novect 1230 fire extinguishing agent does not produce harmful substances during the fire extinguishing process, is harmless to the environment, and will not cause harm to personnel.

No plumbing required: The hanging novect 1230 extinguisher does not require any extinguishing agent piping, making it easy to install and suitable for a wide range of applications.

Temperature control fire extinguishing: The hanging novect 1230 fire extinguisher temperature control model can automatically trigger the fire extinguishing when the fire occurs and the temperature reaches 68 degrees, improving the fire extinguishing efficiency.

How to use:

Installation: Suspend the novect 1230 fire extinguisher over the area that needs to be protected, ensuring that the nozzle of the fire extinguisher can cover the area that needs to be protected.

Commissioning: After installation, the fire extinguisher needs to be commissioning to ensure that it can work properly in the event of a fire.

Maintenance: The hanging novect 1230 fire extinguisher is inspected and maintained regularly to ensure that it is in good working order.

It should be noted that although the hanging novect 1230 fire extinguisher has many advantages, it also needs to be operated in accordance with the requirements of the manual during use to ensure its safety and effectiveness. At the same time, it is also necessary to choose the appropriate model and specification according to the actual situation of the specific place to achieve the best fire extinguishing effect.

Technical parameter

Model	XQFC10/1.6-XL
Agent	Novect1230
Executive standard	GT/CECS10171-2022
Working temperature range	0°C~+50°C
Storage pressure	1.6MPa(+20°C)
Max working pressure	2.5MPa(+50%)
Fire extinguishing design concentration	6.5~8%
Max filling rate	≤1200KG/M ³
System spray time	Computer room ≤8S, other ≤10S

Company profile

Guangzhou Xinlin Firefighting Equipment Co., Ltd. is located in Guangzhou, a vital city connecting China to the world, characterized by its convenient transportation and picturesque environment. We are a manufacturing company with a professional and seasoned team of employees, consisting of solution design experts, technical installation specialists, quality inspection professionals, and after-sales service teams, dedicated to the research and development of HFC-227ea (FM200), IG541, IG100, and Novect 1230 products.

Currently, we offer a range of commonly used fire suppression systems, including FM200 fire suppression systems, cabinet-style FM200 fire suppression systems, fully automatic fire extinguisher (hanging), portable fire extinguisher, IG541 fire suppression systems, IG100 fire suppression systems, fire detection tube fire suppression systems, as well as automatic fire extinguishing pipelines.

With high quality products, perfect service and good reputation, the company has won wide praise from customers at home and abroad.



Why choose us

- Efficient management system
- More than 10 years of experience in gas fire fighting industry
- Advanced equipment and professional engineers
- We provide 8x6 hr technical support and after-sales service

FAQ

Brand name: Guangzhou Xinlin Firefighting Equipment Co., Ltd.

Model: 4KG/6KG/8KG/10KG/20KG/30KG

Place of Origin: Guangzhou City, Guangdong Province, China

Q: What is the NOVEC 1230 fire suppression system?

Answer: NOVEC 1230 (Fk-5-1-12) fire extinguishing system is a clean agent fire extinguishing system, a colorless and odorless gas that is easy to vaporize and will not cause secondary pollution.

Q: What is the brand name of this product?

Answer: Guangzhou Xinlin Firefighting Equipment Co., Ltd.

Q: What are the different models of NOVEC 1230 fire suppression systems?

Answer: The different models of hanging temperature sensing models include 4KG, 6KG, 8KG, 10KG, 20KG and 30KG

Q: Where is this product produced?

A: This product is manufactured in Guangzhou City, Guangdong Province, China.

Q: How does the NOVEC 1230 fire suppression system work?

Answer: NOVEC 1230 liquid is expelled as a gas and quickly penetrates the entire protected area, extinguishing the fire by removing heat energy from the fire.



Guangzhou Xinlin Fire Fighting Equipment Co., Ltd.



189-3396-3312



shirley@gas-firesuppression.com



gas-firesuppression.com

Factory Building in Pozhong (Local Name), Dongzhou Village, Xintang Town, Zengcheng District, Guangzhou, Guangdong, China